SPEQTRIS SPORT | TECHNICAL SHEET B 0

SPECTRIS

SPEQTRIS SPORT | TECHNICAL SHEET

EROS

EROS has a conventional design hiding formidable efficiency. Generally installed in spaces where the practice of sport is eclectic, its Zenithal lighting ensures soft and diffuse light, facilitating all sporting practices. With integrated rotating bracket, simple connection, through and quick: it is certainly a best seller.



Zenithal lighting

DALI

Impact resistance

Simple connections

Through connection


Rotating bracket

(+30/-30°)

Protective grid



Power	Lumens	Dimensions (mm)			
		А	В	С	Weight
120W	19 200 lm	1320	76	238	8.60 Kg
200W	32 000 lm				





Specifications

Series Code	EROSXXX	
Efficacy	160 lm / Watt	
ССТ	4000 K (3000K, 5000K optional)	
CRI	RA > 80	
Input Voltage	AC 120-240 V • 50-60 Hz	
Power Factor	0,92	
Photobiological risk	RG1	
ULR	< 1%	
THD	< 20 %	

Materials	Aluminium / Polycarbonate
Current	Direct current
Driver	Integrated and non-deportable
Driver Brand	Sosen
Dimmable	Dali
Lens	Symmetrical 90°, 60° on request
Colour	White
Standards	IP20 / IK10 / CE / ROHS
Warranty	5 years

serie

EROS



EROS is ideal for:





